

Radar measurement Micropilot NMR84

For high accurate non-contact level measurement in stilling well applications in custody transfer



More information and current pricing:

www.endress.com/NMR84

Benefits:

- Hardware and software developed according to IEC 61508 up to SIL3 (in homogeneous redundancy) for high level of safety
- Maximum reliability through accuracy up to $\pm 0.5\text{ mm}$ ($\pm 0.02\text{\"}$)
- Developed according to international metrology recommendations such as OIML R85 and API MPMS
- Local and country-specific certifications like NMI or PTB for custody transfer applications
- Simplified installation and trouble-free operations due to easy connection to major DCS systems via open protocols
- Unique drip-off antenna design eliminates measurement error due to condensation build-up

Specs at a glance

- **Accuracy** up to 0.5 mm
- **Process temperature** $-40^{\circ}\text{C} \dots 150^{\circ}\text{C}$ ($-40^{\circ}\text{F} \dots 302^{\circ}\text{F}$)
- **Process pressure / max. overpressure limit** Vacuum ... 25 bar abs
- **Max. measurement distance** 50 m (164 ft) For calibration to regulatory standards: 50 m (164 ft)
- **Main wetted parts** 316L, PTFE

Field of application: Micropilot NMR84 is used for custody transfer and inventory control applications with NMI- and PTB-approvals. It meets the relevant requirements according to OIML R85 and API 3.1B. The NMR84 free space radar with drip-off planar antenna is specifically suited for

stilling well applications. The superior drip-off antenna design with proven track record eliminates problems caused by condensation.

Features and specifications

Continuous / Liquids

Measuring principle

Level radar

Characteristic / Application

Planar antenna, 6GHz: High precision measurement for storage tanks up to 30 m (98ft)

Specialities

Custody transfer level measurement

Supply / Communication

85-264VAC

52-74VAC

19-64VDC

Accuracy

up to 0.5 mm

Ambient temperature

Standard:

-40°C...60°C

(-40°F...140°F)

For calibration to regulatory standards:

-25°C...55°C

(-13°F...131°F)

Process temperature

-40°C...150°C

(-40°F...302°F)

Process pressure / max. overpressure limit

Vacuum ... 25 bar abs

Continuous / Liquids**Main wetted parts**316L, PTFE

Process connection

Flange:

DN100/4"...DN300/12"

UNI-Flange:

DN150/6"...DN300/12"

Max. measurement distance

50 m (164 ft)

For calibration to regulatory standards:

50 m (164 ft)

Communication

Outputs:

Fieldbus: Modbus RS485, V1, WM550

HART, BPM and TRL/2 (via GE option)

Analog 4-20mA output (Exi/ Exd)

Relay output (Exd)

Inputs:

Analog 4-20mA input (Exi/ Exd)

2-, 3-, 4-wire RTD input

Discrete input (Exd, passive/ active)

Certificates / Approvals

ATEX, FM, IEC Ex, EAC, JPN Ex, KC Ex,

INMETRO, NEPSI, UK Ex

Safety approvals

Overfill protection WHG

SIL

Design approvals

EN 10204-3.1

NACE MR0175, MR0103

AD2000

Continuous / Liquids

Metrological approvals and certificates

OIML, NMI, PTB

Options

Redundant fieldbus

Alu-coated or 316L housing

Weather protection cover

Application limits

Maximum measuring range is
dependent on the tank form and/
or application

Strong condensate or build-up
formation

More information www.endress.com/NMR84